



DURAFLEX TL PVC



Reference	DFP
Material	PVC
Width	8 mm
Height	30/35/40/50/65
Length	2.5 m
Colour	Height 50 and below: Grey/white/beige/black/terracotta/transparent grey Height 65: grey
Load	Heavy loads, industrial floors
ZDB (German Construction Federation) Information Sheet	Stress group III/wheel stress up to 3N/mm ²
Chem. Resistant	e.g. oil, petrol, ethanol STRONG PVC PROPERTIES 1009 Value: 80, STANDARD: DIN53505 Value: V0, STANDARD: UL94 elastic hardness unit of measurement
Properties Shore hardness Flame behaviour	STRONG PVC PROPERTIES 1009 Value: 80, STANDARD: DIN53505 Value: V0, STANDARD: UL94 elastic hardness unit of measurement
Shore hardness	PVC FLEXIBLE 1070 Value: 75, STANDARD: DIN53505 Elastic hardness unit of measurement
Figure	

Indications

The following applies to all products/materials: Usability in terms of mechanical and chemical stress should always be checked carefully before installation.

DURAL GmbH
 Südring 11
 D-56412 Ruppach-Goldhausen
 Tel. +49 (0) 2602/9261-0
 Fax +49 (0) 2602/9261-50
 info@dural.com